

PORT NAME: SIKKA RELIANCE TERMINAL

UN Code: IN SIK ■ Mode: BERTH + SPM ■ Lat: 22°34.3'N Long: 069°45.8'E ■ BA Charts: 2033 & 2083 ■ ISPS: Security Level 2

■ PORT GENERAL INFO

VHF Channel	Night Navigation
16 / 71	Permitted
Pilot Boarding	Manoeuvring Time
Mandatory	2 Hours
Anchorage	Tidal Port
Ch. 16 / 71	Yes
Gangway	Water Density
Applicable	1.023–1.025 WOG
Ship Crane Outreach	Floating Crane
N/A	Available
Shore Crane	Grabs
Not Available	Not Available

■ PORT RESTRICTIONS

Parameter	Berth	SPM
Max Draught	14.50 m	22.50 m
Max LOA	252 m	345 m
Max Beam	45 m	N/A

■ FACILITIES

Bunker	Fresh Water
Available	Not Available
Sludge Disp.	Garbage Disp.
Not Available	Not Available
Provision	Repairs
Available (via agent)	Available (via agent)
Hold Cleaning	Crew Change
Not Available (via agent)	Available*

*Restricted: China, Pakistan, Bangladesh, Korea, Sri Lanka

■ NEAREST AIRPORTS

Airport	Type	Code	Dist.
Jamnagar	Domestic	JGA	~28 km
Rajkot	Domestic	RAJ	~123 km
Ahmedabad	International	AMD	~346 km

■ STEVEDORE SHIFTS (24x7)

Shift	Hours
1st Shift	0800 – 1600 hrs
2nd Shift	1601 – 2400 hrs
3rd Shift	0001 – 0800 hrs

■ COMMUNICATION

VHF	ISPS Level
Ch. 16 / 71	2
Night Nav	Tidal
Permitted	Yes

PORT NAME: SIKKA RELIANCE TERMINAL

UN Code: IN SIK ■ Mode: BERTH + SPM ■ Lat: 22°34.3'N Long: 069°45.8'E ■ BA Charts: 2033 & 2083 ■ ISPS: Security Level 2

■ BERTH PARAMETERS

Berth	Draught (m)	LOA (m)	Beam (m)	Displ.	Manifold	Cargo Rate	Commodities
A-1	11.5	195	45	59,850	12" 150ASA	350/150/800 m³/hr	Paraxylene, Orthoxylene, Diesel, Motor Spirit, Naphtha, Methanol
A	12.5	195	45	59,850	12" 150ASA 8-10" 300ASA (LPG)	350/280/800 m³/hr	Paraxylene, Benzene, Diesel, Motor Spirit, Naphtha, LPG, Butane, Propane, Alkylate
B	13.5	230	45	86,450	12" 150ASA	350/280/800 m³/hr	Paraxylene, Benzene, TAME/Reformate (AFS), Diesel, Motor Spirit, ATF, Naphtha, Alkylate
C	13.5	246	45	1,12,500	12" 150ASA 8-10" 300ASA	800 m³/hr	TAME/Reformate (AFS), Diesel, Motor Spirit, ATF, Naphtha, LPG, Butane, Propane, Alkylate
D	14.5	252	45	1,20,000	12" 150ASA	800/200 m³/hr	Diesel, Motor Spirit, ATF, Naphtha, HPP Crude / VGO / F.O.

■ SPM (SINGLE POINT MOORING) PARAMETERS

SPM	Draught (m)	LOA Range (m)	Displacement	Manifold	Cargo Rate	Commodity
SPM-1	22.5	228-345	40,000	2x20" 150ASA	8,000 m³/hr (single) / 14,500 m³/hr (double)	Crude
SPM-2	22.5	228-345	40,000	2x20" 150ASA	8,000 m³/hr (single) / 14,500 m³/hr (double)	Crude
SPM-3	22.5	228-345	40,000	2x20" 150ASA	8,000 m³/hr (single) / 14,500 m³/hr (double)	Crude
SPM-4	18.5	180-300	1,70,000	2x16" 150ASA	4,500 m³/hr (1 hose) / 9,000 m³/hr (2 hoses) Min start/topping: 1,000 m³/hr	Motor Spirit
SPM-5	18.5	180-300	1,70,000	2x16" 150ASA	4,500 m³/hr (1 hose) / 9,000 m³/hr (2 hoses) Min start/topping: 1,000 m³/hr	Motor Spirit

Sikka Reliance Terminal — Port Information Sheet | Data subject to change. Verify with port authority before operations.